ADLOIS F, SPECIAL ADHESIVE FOR CERAMICS AND STONE



Descrição

Dust adhesive that mixed with AGLUTAIS 30 - 50 makes it in a ideal adhesive for sitting marble, granite and stone on regularized supports. Available colours: White or grey.

Aplication

ADLOIS F is used as an adhesive in the stone fixed elements and for placing ceramics pieces in top of each other.

Surface preparation

The surface which the product is going to be applyed must be cleaned, dust free and free particles. Must be strong and porous. The support must be slaightly moistened before applying.

Modes of application

Adois F is mixed in this proportions:
-Mix ADLOIS F and AGLUTAIS 30-50 in this way: 25 kgs of ADOIS with 4 litres of AGLUTAIS 30-50 until obteining a homogenize and consinstent paste.
The product mix is realized manually or with a low speed electric mixer (400-500 rpm).

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

-In summer time with hot weather, don´t spread more material than it could be covered in 10 minutes. The product can be open more time when more cold the weather is.
In winter time the open-time can be of 20 minutes.
Apply by thooted trowel in thickness about 2-5 mm.

Clean up

With a lot of water while the material is still fresh. The hardened material only can be removed by mechanical means.

Data sheet

Water Absorption26 ± 2% (Aglutais 30-50)

Powder Density1,200 ± 0,05 g/cc.

Bulk Density1,750 ± 0,05 g/cc.

Curing Density1,8 ± 0,05 g/cc.

Adhesion> 1,0 N/mm2

Performance

3 kg per sqm by 2 mm layer.

Storage

2 years in they sacks and original containers. Well closed and keep in dry and open-air environments.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: