CECOIS YESO, ADHESIVE FOR PLACING CERAMICS ON GYPSUM PLASTERING



Descrição

Powder glue-cement in white colour that just mixed with water in the moment of using, is an excellent adhesive for placing tiles, bricks, trims, on gypsum supports, plasterboards and similars. Used only for indoors. Prices according the volume of order.

Aplication

CECOIS YESO is used only on indoors as an adhesive on the placing of bricks, tiles, etc and on gypsum-plaster, plasterboar and similars too. In case of gypsum- plaster supports is recommendended the used of AGLUTAIS 30-50 instead of water.

Surface preparation

It must be uniform, smooth, clean, free of greases, oils, dust, tightly dry and compact.

Modes of application

Ready to mix with water until achieve a manoeuvrable paste.
-Mixture must be of 8,5 litres by each 25 kgs CECOIS YESO sack.
-Mix manually or mechanically with an electric mixer (300 to 500 rpm).
-Let it rest from 3 to 5 minutes before using.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

It must be spreading by a trowel witt 15 of working time to apply the coating on the support. In hot weather the open time is lower so is recommendable just open the properly quantity of product that will be used in open time.
Is recommendable to spread the product on small areas if the surface is big.

Clean up

Plenty of clean water while the material is wet.

Data sheet

Powder Density1,25 ± 0,050 g/cc.

Bulk Density1,700 ± 0,050 g/cc.

Curing Density1,650 ± 0,050 g/cc.

Water Absorption28 ± 3%

Adhesion> 0,5 N/mm2

Color(s)Grey white.

TypeC1 according UNE EN 12004

Performance

3 kg per sqm in 2mm layer.

Storage

2 years in their original packages, tightly closed, keeping away from high temperatures, protected against the weather and in dry and open-air places.

Security



TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

Indications of danger:

H315: H315:Causes skin irritation.

H317: H317:May cause an allergic skin reaction.

H318: H318:Causes serious eye damage.

H335: H335:May cause respiratory irritation.

Prudence advice:

P261: P261:Avoid breathing dust/fume/gas/mist/vapours/spray.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: P302+P352:IF ON SKIN: Wash with plenty of soap and water.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: P321:Specific treatment (go to see a doctor with the Safety data sheet for this product).

P405: P405:Store locked up.

P501: P501:Dispose of contents/container in accordance with local/regional/national/international regulation