CECOIS PISCINAS SUPER BLANCO, ADHESIVE FOR CERAMIC TILES ON POOLS.



Description

Cement-based adhesive specially designed for pools that mixed with water just in the moment of using, becomes in a suitable adhesive for cladding applying (glazzed or ceramics) on pools. Super White colour for making the grout easier.

Aplication

Fitting and grouting of claddings on pools, fitting of glazed claddings and in wet areas such bath-rooms or kitchens.

Surface preparation

The surface must be clean, free of greases, mold releases wastes, compact without scuffs and slighty dampened.

Modes of application

Mix directly with water in the recommended proportion until ahieve a thick consistency.
-The proper mixture is 6,25 litres of water by 25 kgs sack.
-The mix can be done manually or with slow speed electric mixer(400 to 500 rpm).

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

-The adhesive must be spreading on the support with a toothed trowel, spreading the product according with open time of the product (15 to 20 minutes according the temperature).
-Place the pieces pressing them in order to achive that the adhesive becomes smooth.
-In hot weather time or when the support is highly absorbent the slightly is recommedable to damp it slightly before applicating.

Clean up

Plenty of water while the material is wet. If it becomes hardened only with mechanical means can be removed.

Data sheet

Water Absorption25+/- 3%

Adhesion> 0,5 N/mm2

Color(s)White super.

Curing Density1,650 g/cc

Bulk Density1,850 g/cc

Powder Density1,250 g/cc

Performance

3 kg per sqm in 2 mm layer.

Storage

2 years in their original sacks, tightly closed avoiding extrem temperatures, keeping away from the weather and in dry and open-air places.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: