UNIRRES-NC UNIVERSAL, UNIVERSAL ADHERENCE IMPROVER AGENT WHICH DOESN´T PRODUCE CORROSION ON METALS



Description

UNIRRES-NC is a bonding agent to apply on metallic, wooden surfaces and with mortars, paints, etc. Due its special formulation it doesn´t produce corrosion on ferrous metals.

Aplication

UNIRRES NC is applied to obtain a suitable adherence between supports mainly metallic, wooden surfaces, paints and cement-based mortars, lime or gypsum.

Surface preparation

The surface where the product is applied must be cleaned, free of greases, without rust and dry.

Modes of application

UNIRRÉS NC is ready to use and no requires dilution.
-The product must be homogenized before applying.

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

-Spread a thin coat of the product on the surface by a brush or paint-brush.
-The inital applied product is white and becomes traslucent when is ready to mix it whith mortar (mortar must be applied while the product is sticky.
-The temperature of application must be from 5 to 40ºC.

Clean up

With plenty clean water.

Data sheet

AppearanceLiquid

Color(s)White

Density1,02 kg/lt

Solids Content

Adhesion

Adhesion

Performance

From 4 to 5 sqm per litre

Storage

1 year in their original package. Tightly closed without exposing it to extrem temperatures, protected from the weather and in dry and open-air places.

Security

Supplementary information:

EUH208: EUH208:Contains . May produce an allergic reaction.

EUH210: EUH210:Safety data sheet available on request.