



# COLTE, COLOURED ADHESIVE FOR THE PLACEMENT OF TILES AND GABLE ENDS



## Descripción

Coloured cementitious adhesive for the placement of tiles and gable ends. COLTE is presented in the most characteristics colours of tiles in order to improve the aesthetic appearance.

## Aplication

COLTE is used for the placement of tiles and roof ends.

## Surface preparation

The surface of placement must be clean, free of dust and firm.

## Modes of application

Colte is mixed with water until obtain a homegeneous paste. The mixture must be done with a low-speed electric mixer with helicoidal pallets in order to avoid the air in the mixture.

- The quantity of water is 5 litres per sack of 25 kgs.
- Let rest a few minutes before placing.
- Fix the adhesive on the tile preessing on it in order to fit it in the right position.

## Clean up



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:



With plenty clean water while the material is wet.

# Data sheet

---

Water absorption 18 a 20%

Adherence > 0,5 N/mm<sup>2</sup>

Curing density 1,7 kg/lt

Colour/s Creme, red-tile, brown.

## Performance

---

From 3 to 4 sqm per sack of 25 kgs.

## Storage

---

2 years in their original packages, tightly closed and keeping from the weather.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

