



COLTE, COLOURED ADHESIVE FOR THE PLACEMENT OF TILES AND GABLE ENDS



Descripción

Coloured cementitious adhesive for the placement of tiles and gable ends. COLTE is presented in the most characteristics colours of tiles in order to improve the aesthetic appearance.

Aplication

COLTE is used for the placement of tiles and roof ends.

Surface preparation

The surface of placement must be clean, free of dust and firm.

Modes of application

Colte is mixed with water until obtain a homegeneous paste. The mixture must be done with a low-speed electric mixer with helicoidal pallets in order to avoid the air in the mixture.

- The quantity of water is 5 litres per sack of 25 kgs.
- Let rest a few minutes before placing.
- Fix the adhesive on the tile pressing on it in order to fit it in the right position.

Clean up



With plenty clean water while the material is wet.

Data sheet

Water absorption 18 a 20%

Adherence > 0,5 N/mm²

Curing density 1,7 kg/lt

Colour/s Creme, red-tile, brown.

Performance

From 3 to 4 sqm per sack of 25 kgs.

Storage

2 years in their original packages, tightly closed and keeping from the weather.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

