

## ADIRRES, BONDING AGENT FOR **SURFACES WITH LOW ADHERENCE**



# **Description**

Bonding agent to apply on supports with low adherence. Its application allows the application on ceramic surfaces both walls and floors for the subsequent application of screeds, levelling pastes, cement-base adhesives, etc.. Very suitable as bonding agent on floors because it doesn't have tacking.

# **Aplication**

Adirres is applied on ceramic supports, wood, and once dry allows the application of levelling pastes and cement-base adhesives for the application of claddings, application of screed layers. Etc

### **Surface preparation**

The surface must be clean, dry, dust-free and loose particles, firm and resistant.

### Modes of application

The content of container must be homogenized.

- -Apply by brush or roller on the clean and dry support.
- -First, apply one coat and let it dry. The applyed coat on the product can not be thick in order to preserve its mircro-rough texture.
- -Drying time for mortar or cement-base adhesive application should be 12 hours at list at 20°C and 65%





HR(relative humidity).

- -Once dry, proceed to the levelling pastes or mortars application for floors and cement-base adhesive or thixotropic mortars in case of walls.
- -Water should not added to the product.

### Clean up

Tools must be cleaned with plenty of water while the material is wet.

## Data sheet

Colour/sLight yellow.

Density0,93 Kq/Lt

AspectViscous liquid.

Drying time 12 hours for mortar or glue cemment application

Temperature of work20°C and 65 Relative Humidity.

#### **Performance**

4 sqm/Lt

## **Storage**

Two years in their original packages protected from the weather and stored in a dry and fresh place.

# Security

## **Supplementary information:**

EUH208: Contains . May produce an allergic reaction.






Email.: desarrollo@teais.es

EUH210: Safety data sheet available on request.





15143 Arteixo, A Coruña

