



# CONTACTIS AQUA, Water contact adhesive

## Descripción

Water-based contact adhesive for fixing many types of supports, absorbent and no absorbent. It is applied by brush on both sides of the elements to fix. Let the piece to air and press it until the adhesive is dried,



## Aplication

Glued expanded polystyrene, extruded, polyurethanes, textile, plastics, carpets, linoleum, PVC, etc.

## Surface preparation

The support must be clean, dry, free of dust or loose particles.

## Modes of application

- Homogenize the content of the package.
- Apply by brush on both sides of the surfaces to fix.
- Let the piece to air properly. Press both sides.

## Clean up



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: desarrollo@teais.es

síguenos en:



The tools are cleaned with water while the material is fresh.

# Data sheet

Colour/sWhite when it's wet. Translucent when it's dry.

Adherence > 1 N/mm<sup>2</sup>

Density 1 kg/lt

Totally dry 6 hours at 20°C

## Performance

1sqm/litre according the absorption of the support

## Storage

Two years in its original containers protected from the elements, stored in a cool and dry place.

## Security

## Supplementary information:

EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:

