



# EPOAIS METAL HIERRO, Filler and adhesive EPOXI with metallic appearance.



## Descripció

EPOAIS METAL HIERRO is a two-component adhesive and filler Epoxi. It has high adherence on several supports, very high mechanical resistance and metallic appearance similar to iron.

## Aplicación

EPOAIS METAL HIERRO is very suitable such as adhesive for several supports (metallic, wood, glass, vitrifieds, etc) and such as a filler material with high adherence and high mechanical resistance properties.

## Surface preparation

The support of application must be clean and dry, free of dust and loose particles.

## Modes of application

Homogenize each component separately.

-Mix both component in proportion 1:A 1:B percentage by weight or volume.

-Apply with spatula in the surface. After that smooth and clean the waste with EPÒXI SOLVENT before material becomes dry.

## Clean up



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: desarrollo@teais.es

síguenos en:



The tools used in the manipulation of the product must be cleaned with EPOXI solvent.

# Data sheet

---

Density 4,15 kg/lt

Colour/s Metal grey

Open time 30 minutes at 20°C

Drying time 12 hours at 20°C

## Performance

---

4 kg/litre of volume for filling

## Storage

---

2 years in their original packages keeping away from weather, stored in a cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email.: desarrollo@teais.es

síguenos en:

