



EPOAIS METAL HIERRO, Filler and adhesive EPOXI with metallic appearance.



Description

EPOAIS METAL HIERRO is a two-component adhesive and filler Epoxi. It has high adherence on several supports, very high mechanical resistance and metallic appearance similar to iron.

Application

EPOAIS METAL HIERRO is very suitable such as adhesive for several supports (metallic, wood, glass, vitrifieds, etc) and such as a filler material with high adherence and high mechanical resistance properties.

Surface preparation

The support of application must be clean and dry, free of dust and loose particles.

Modes of application

Homogenize each component separately.

-Mix both component in proportion 1:A 1:B percentage by weight or volume.

-Apply with spatula in the surface. After that smooth and clean the waste with EPÒXI SOLVENT before material becomes dry.

Clean up



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teis.es

síguenos en:



The tools used in the manipulation of the product must be cleaned with EPOXI solvent.

Data sheet

Density 4,15 kg/lit

Colour/s Metal grey

Open time 30 minutes at 20°C

Drying time 12 hours at 20°C

Performance

4 kg/litre of volume for filling

Storage

2 years in their original packages keeping away from weather, stored in a cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

