



CECOISFLEX FRAGUADO RAPIDO, FLEXIBLE GLUE CEMENT WITH MIXED BINDERS AND FAST SETTING.



Descripción

CECOISFLEX FRAGUADO RÁPIDO is a flexible cement-based adhesive suitable for sticking ceramics. It has high adherence, deformation capacity, suitable for placing facades, big pavements, pieces of marble, ceramics, stone, granite of big and small format, absorbent and no-absorbent, plasterboard panels, heat radiant floors, for indoors and outdoors.

Aplication

The product is used in all types of ceramic tilling : stone, marble, granite, big and small format, absorbent and no-absorbent, plasterboards, radiant heating floors, for indoors and outdoors.

Surface preparation

The support must be clean, firm, free of greases, without grout wastes, cured (more than 28 days) and dry.

Modes of application

CECOIS FLEX FRAGUADO RÁPIDO is mixed with water in proportion of 6 litres of water by 25 kgs sack approximately.

-The mixture can be manually, but is recommended to use a low-revolution electric mixer (from 300 to 500 rpm).



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:

- Let rest the mixture 2 minutes and after must be spreaded on the support in small areas (1 sqm maximum).
- First apply the adhesive with a toothed trowel, after that the pieces must be placed and pressing them in order to obtain a smooth surface without furrows.
- In pieces bigger than 30x30 cm must be done with double application of CECOIS FLEX.

Clean up

The tools must be cleaned with plenty of water before the material becomes harder.

Data sheet

Water absorption 24% +/- 2

Adherence > 1 N/mm²

Curing density 1,650 kg/lt

Powder density 1,280 kg/lt

Mass of density 1,880 kg/lt

Colour/s White and grey

Performance

3 KG per sqm in 2 mm layer.

Storage

One year in their original packages, keeping away from the weather and stored in a cool and dry place.

Security



Indications of danger:

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

Prudence advice:

P261: Avoid breathing dust.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (go to see a doctor with the Safety data sheet for this product).

P405: Store locked up.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains: Cement, portland, chemicals. May produce an allergic reaction.