



AGLUTAIS 30-50 RÁPIDO, PLASTIC RESIN TO IMPROVE AND ACCELERATE SETTING MORTAR AND CONCRETE.



Description

Thixotropic emulsion based on synthetic resins that when they are added directly with mortars and concretes masses, confers an increase of physical and chemical resistances and also reduces the setting time. It must be added slowly with mortar until get the proper thickness. It avoids the cracking of renders. It is stable in wet environments. It's anticorrosive and reduces the dust formation.

Application

Bonding mortars to concrete plaster facades weak pressurized water for repairs and patching mortars requiring fast setting, in mortars and homigones where demands shorten startup times, etc..

Surface preparation

Not Applicable

Modes of application

Clean up

Clean with a lot of water



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:

Data sheet

Density

Colour/s

Performance

In mortars 26 l by 100 kg of cement.

Storage

Three years, in their original containers, tightly closed, without exposing to extreme temperatures, protected from the weather and in dry and ventilated.

Security

Supplementary information:

EUH208: EUH208:Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210: EUH210:Safety data sheet available on request.