



# AGLUTAIS 30-50 RÃ• PIDO, PLASTIC RESIN TO IMPROVE AND ACCELERATE SETTING MORTAR AND CONCRETE.



## Descripción

Thixotropic emulsion based on synthetic resins that when they are added directly with mortars and concretes masses, confers an increase of physical and chemical resistances and also reduces the setting time. It must added slowly with mortar until get the proper thickness. It avoids the cracking of renders. It is stable in wet environments. It's anticorrosive and reduces the dust formation.

## Aplication

Bonding mortars to concrete plaster facades weak pressurized water for repairs and patching mortars requiring fast setting, in mortars and homigones where demands shorten startup times, etc..

## Surface preparation

Not Applicable

## Modes of application

## Clean up

Clean with a lot of water



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:



# Data sheet

Density

Colour/s

## Performance

In mortars 26 l by 100 kg of cement.

## Storage

Three years, in their original containers, tightly closed, without exposing to extreme temperatures, protected from the weather and in dry and ventilated.

## Security

## Supplementary information:

EUH208: EUH208:Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210: EUH210:Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teis.es](mailto:desarrollo@teis.es)

síguenos en:

