



IAIS, PLASTICIZER AND WATERPROOFING LIQUID FOR CONCRETES AND MORTARS



Descrição

Water-repellent liquid additive and workability improver for mortars.

Aplication

Improves with efficiency the waterproofing and workability of mortars and concretes. For all purposes.

Surface preparation

It is no necessary

Modes of application

lais is added into water-mixed in the proportion of 1 litre per 100kgs (2 sacks) of cement.

It is recommendable to use mortars and concretes richs in cement, cleaned sand from rivers or quartz with particle-size from 0 to 2 mm and continuous granulometric curves.

Clean up



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



With plenty clean water.

Data sheet

Colour/sWhite

Density1 Kg/L.± 0,10 g/cm³. at 20°C

Viscosity60 ± 15 seg. at 20°C Ford Cup 4mm.

PH13 ± 1

Performance

1 lt for each 400 kg of cement.1 lt for each 200kg

Storage

For 1 year in their original packages, tightly closed, in a dry place, cool and at temperatures over 0° otherwise if it is exposed to lower temperatures it would cristllize without recovery.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

