

RETARDOIS, SETTING-TIME RETARDANT FOR CONCRETES AND MORTARS.



Descripción

Colourless liquid and setting time-retardant of cement and concretes. Perfect for delay the setting-time when the enviroment conditions requires it or in that cases which a longer open-time than usual is required.

Aplication

RETARDOIS is suitable for delaying the setting-time, with hot weather, when a big quantity of concrete to place is required, when it requires to avoid the concreting joints, when it transported over long distances, with bad conditions for placing, when it is requires to increase the workability-time, etc.

Surface preparation

It is no necessary.

Modes of application

Shake the content of the package in order to homogenize it before using.

-RETARDOIS must be added to water but in a proportion less than 1,5% in cement weight used (maximum dose must be 0,40 litres per cement sack). It is recommended a previous test in order to achieve the setting-time delay required.





Clean up

With plenty of water.

Data sheet

Colour/sColourless.

Density1,1 Kg/L. (+-) 0,05 at 20°C

Viscosity4 ± 1 sec to 20°C. Ford coat: 4mm.

Solid content10% aprox.

PH7 aprox.

Performance

From 0,125 to 0,400 l per cement sack.

Storage

In their original packages, tightly closed, in a dry and cool place for 3 years.

Security



Indications of danger:

H317: May cause an allergic skin reaction.

Prudence advice:





P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation



