



# HIDRO 1, WATERPROOFING FOR MORTARS AND CONCRETES



## Description

White liquid additive used for making waterproofing mortar and concrete.

## Application

Hydro-1 it's used to improve the impermeability of concretes and mortars.

The mortars and concretes added with Hydro-1 can be used in coatings of water tanks, swimming pools, facades, foundations, basement walls. Suitable for underground works, tunnels, galleries, foundations, retaining walls, canals, irrigation ditches, etc.

## Surface preparation

Not applicable

## Modes of application

Mix well the product prior to its implementation.

- Hydro-1 is added directly to the concrete or mortar, in the proportion of 0.5 liters per sack of cement.
- The mortar should be rich in cement 1: 3 (cement: sand).



Avda. da Enerxía, nº 153, PoL Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: desarrollo@teais.es

síguenos en:

- The additive does not affect the process of hardening of the mortar or concrete nor adhesion between layers nor terminating resistors.
- Cements used must be cool and dry.

## Clean up

With plentiful clean water

## Data sheet

AspectWhite liquid

Density1,0 - 1,1 gr/cc.

PH9 - 11

Solid content>10%

## Performance

0,5 liter per bag of cement.

## Storage

During 1 year in their original packagings, tightly closed, in dry and fresh places, at higher temperatures than 0º C.

## Security

## Supplementary information:

EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.



Avda. da Enerxía, nº 153, PoL Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email.: desarrollo@teais.es

síguenos en: