HIDRO 1, WATERPROOFING FOR MORTARS AND CONCRETES



Description

White liquid additive used for making waterproofing mortar and concrete.

Aplication

Hydro-1 it's used to improve the impermeability of concretes and mortars.
The mortars and concretes added with Hydro-1 can be used in coatings of water tanks, swimming pools, facades, foundations, basement walls. Suitable for underground works, tunnels, galleries, foundations, retaining walls, canals, irrigation ditches, etc.

Surface preparation

Not applicable

Modes of application

Mix well the product prior to its implementation.
- Hydro-1 is added directly to the concrete or mortar, in the proportion of 0.5 liters per sack of cement.
- The mortar should be rich in cement 1: 3 (cement: sand).

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

- The additive does not affect the process of hardening of the mortar or concrete nor adhesion between layers nor terminating resistors.
- Cements used must be cool and dry.

Clean up

With plentiful clean water

Data sheet

AppearanceWhite liquid

Density1,0 - 1,1 gr/cc.

pH9 - 11

Solids Content>10%

Performance

0,5 liter per bag of cement.

Storage

During 1 year in their original packagings, tightly closed, in dry and fresh places, at higher temperatures than 0º C.

Security

Supplementary information:

EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: