

# MICROEXPAN, EXPANSIVE AND PLASTICIZER ADDITIVE FOR GROUTS AND MORTARS



## Descripción

Expansive and plasticizer additive for concrete groutings and for improving mortars. It provides high fluency groutings an low relationship between water/cement which improves the setting. In case of using mortar it improves the workability and reduces its plastic contraction.

## Aplication

Microexpan can be used in the filling of foundations, groutings, non retraction fillings, etc.

## Surface preparation

The application surfaces must be clean, healthy, slightly moistened.

## Modes of application

Add the required amount of water to the mixing container or concrete mixer. Then slowly add cement, sand and MICROEXPAN.

Slowly mix during 5 minutes until finally obtaining a uniform and fluid mix.

- Apply the mortar within 20 minutes after mixing.
- The mortars should undergo proper curing so that they may be protected against premature drying, by

spraying them.

## Clean up

---

With plenty of water, while the material is not hardened.

## Data sheet

---

Aspect Greyish powder.

Density 1.167 kg/l

## Performance

---

275 grs per 75 kg of cement.

## Storage

---

1 year in original packaging protected from weather, in a dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

