



# ADITEX, TEXTURIZER ADDITIVE FOR SYNTHETIC PRODUCTS



## Descripción

Textured additive special for paints and synthetic claddings.

## Aplication

It is used for texturing all kind of coatings or synthetic paints. Mainly in pavements applications, ramps, stairs, which a no-slipping texturized surface must be achieved.

## Surface preparation

The suitable for the application of paint or coating.

## Modes of application

It can be used spreading it on the paints or wet coatings, allowing to rest and removing the loose particles when it is dried and then can be finished with a coating of cladding as a protection.

-Another way to apply is adding the powder to the paint or coating before application removing the mixture in order to homogenize properly the particles and after that apply it by a roll or a paint-brusher. In this case the application must be quick to avoid the particle sedimentation.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:



The mixture always must be removed in order to be sure that the particles are in suspension.

## Clean up

The tools must be cleaned with water.

## Data sheet

AspectTranslucent powder.

Density2,6 grs/cm<sup>3</sup>.

SolubilityWater insoluble.

Point of fusion1300 to 1500°C

## Performance

According to use.

## Storage

Unlimited in their original packages tightly closed, keeping them away from the weather and extrem temperatures.



Avda. da Enerxía, nº 153, PoL Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email.: desarrollo@teais.es

síguenos en: