ADITEX, TEXTURIZER ADDITIVE FOR SYTHETIC PRODUCTS



Description

Textured additive special for paints and synthetic claddings.

Aplication

It is used for texturing all kind of coatings or synthetic paints. Mainly in pavements applications, ramps, stairs, which a no-slipping texturized surface must be achiveded.

Surface preparation

The suitable for the applycation of paint or coating.

Modes of application

It can be used spreading it on the paints or wet coatings, allowing to rest and removing the loose particles when it is dryed and then can be finished with a coating of cladding as a protection.
-Another way to apply is adding the powder to the paint or coating before application removing the mixture in order to homegenize properly the particles and after that apply it by a roll or a paint-brusher. In this case the application must be quick to avoid the particle sedimentation.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

The mixture always must be removed in order to be sure that the particles are in suspension.

Clean up

The tools must be cleaned with water.

Data sheet

AppearanceTranslucent powder.

Density2,6 grs/cm3.

SolubilityWater insoluble.

Melting point1300 to 1500ºC

Performance

According to use.

Storage

Unlimited in their original packages tightly closed, keeping them away from the weather and extrem temperatures.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: