



TEAIS RAPI-COL, Accelerator and activator for glue cement.



Descripción

TEAIS RAPI-COL is an activator energetic additive to improve the setting-time in glue-cements. Suitable for fast-works mainly with cold weather. The product must be added with the water of mixture. It allows placements with low temperatures and make faster the setting. It can be used with all types of glue cements with cementitious bondings.

Aplication

TEAIS RAPI-COL is applied mainly in works that requires a quick starting up or in those that the setting is required to improved because the low temperatures.

Surface preparation

Not Applicable

Modes of application

Homogenize the content of the package.

-Add it to the water on the mixture of the glue cement in a proportion of 20-50% according the temperature and the setting time (The quantity to mix must be higher if the temperature decreases and also if the ready time must be reduced).

Don't mix more product that it can be applied in 10 minutes.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:



- Don't spread more product that can covers more than 1 sqm in order to control the right dampness of the pieces with the adhesive.
- The surface can be crossable from 4 to 8 hours according the temperature and dosification.
- After 12 hours the surface can be stepped on.

Clean up

With plenty of clean water

Data sheet

AspectTraslucent liquid

Density1,12 kg/lit + - 0,1

pH value9

Performance

Used instead of water in the mixt, 1:1 on water.

Storage

3 years in their original packaging tightly closed, protected from the weather and exposed to extreme temperatures, stored in a cool and dry place.

Security

Supplementary information:

EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

