TEAIS LATEX, Emulsion adhesive that improves grouts and mortars.



Description

Adhesive emulsion for mortars or grouts which is mixed with water in order to improve the adherence properties, mechanical resistance, wearing resistance. It improves the waterproofing, reduces the crack risk, provides flexibility and improves chemical resistance.

Aplication

TEAIS LATEX is used for improving adhesive groutings and grouts for clogging pores, masonry mortars in general, glue-cements, low-thickness mortars, to improve adherence on several supports, to improve the elasticity and flexibility. It reduces the crack risk and improves the impermeability, the abrasion resistance and chemical resistances.

Surface preparation

Applitations support must be cleaned, free of greases and oils, grout and paint wastes, loose parts or bad adhered.

Modes of application

For making mortars or grouts a mixture of 1 part of TEAIS LATEX per 2 parts of water must be prepared. This mixture is used for making the preparations.

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

-It must not make dilutions above 1 part of TEAIS LATEX per 2 parts of water.
-The temperature must be higher than 5ºC for any application.

Clean up

The tools must be cleaned with plenty of water before mortars and grouts hardening.

Data sheet

Color(s)Whitish

Density1,04 kg/lt

Solids Content35%

Performance

According to dosification.

Storage

Two years in their original packages keeping them away from the weather, specially from the freeze.

Security

Supplementary information:

EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: