TEAIS TIXO, Thixotropic additive.



Description

TEAIS TIXO is a thixotropic additive for two-component products such as PAVITAIS PI and LASTOIS IP.

Aplication

TEAIS TIXO is used to give thixotropy to products based on resins of two-components (PAVITAIS PI and LASTOIS IP) both epoxy and polyurethane improving the texture to apply as a paint in vertical supports or achieve a doughy consistente to make putties for several applications (half-cane, plaster of cracks, repararation of irregularities).

Surface preparation

Not neccessary.

Modes of application

It is a powder product and must be added in the blend of resins once it´s done.
- For achieve a proper texture for painting a 5% on weight must be added in mixing (PAVITAIS PI and LASTOIS IP).
- For giving a doughy consistence and forming half-cane a 15% on weight of blend must be added (PAVITAIS PI LASTOIS IP).

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

- Homegenize it well manually or mechanically.
- Apply on the admixture opening-time.
- Clean excess with solvent before the admixture hardens.

Clean up

Tools must be cleaned with EPOXY SOLVENT while the product is wet.

Data sheet

AppearanceWhitish powder

Density0,2 kg/lt

Performance

5% on weight for paint and dough texture.

Storage

Two years in their original packages stored in cool and dry places and protected from the weather.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: