



## Descripción

TEAIS TIXO is a thixotropic additive for two-component products such as PAVITAIS PI and LASTOIS IP.

## Application

TEAIS TIXO is used to give thixotropy to products based on resins of two-components (PAVITAIS PI and LASTOIS IP) both epoxy and polyurethane improving the texture to apply as a paint in vertical supports or achieve a doughy consistence to make putties for several applications (half-cane, plaster of cracks, reparation of irregularities).

## Surface preparation

Not necessary.

## Modes of application

It is a powder product and must be added in the blend of resins once it's done.

- For achieve a proper texture for painting a 5% on weight must be added in mixing (PAVITAIS PI and LASTOIS IP).
- For giving a doughy consistence and forming half-cane a 15% on weight of blend must be added (PAVITAIS PI LASTOIS IP).

- Homegenize it well manually or mechanically.
- Apply on the admixture opening-time.
- Clean excess with solvent before the admixture hardens.

## Clean up

---

Tools must be cleaned with EPOXY SOLVENT while the product is wet.

## Data sheet

---

Aspect Whitish powder

Density 0,2 kg/lt

## Performance

---

5% on weight for paint and dough texture.

## Storage

---

Two years in their original packages stored in cool and dry places and protected from the weather.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email.: desarrollo@teais.es

síguenos en:

