TEAIS TERMIC LATEX, Additive improver of cement-based adhesives for radiant heating floorings.



Descripción

TEAIS TERMIC LATEX is an additve which improves the properties of glue-cements for placing tiles on radiant pavements.

Aplication

TEAIS TERMIC LATEX improves substantially the properties of cement-based adhesives for the application of coverings on radiant heating floorings.

Surface preparation

Not neccessary.

Modes of application

Homogenize the content of the package.
- Mix with water in proportion of 1l of TEAIS TERMIC LATEX by each 2 litres of water and mix the cement-base adhesive with this admixture.
- Not apply at temperatures bellow of 8ºC and over 25ºC.

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

Clean up

Tools must be cleaned with water.

Data sheet

Color(s)milky white

Density1,05 kg/lt

Solids Content> 40%

Performance

1 litre per 2 litre of water.

Storage

3 years in their original packages tightly closed and stored in cool and dry place.

Security

Supplementary information:

EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.

TEAIS

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en: