



TEAIS TERMIC LATEX, Additive improver of cement-based adhesives for radiant heating floorings.



Description

TEAIS TERMIC LATEX is an additive which improves the properties of glue-cements for placing tiles on radiant pavements.

Aplication

TEAIS TERMIC LATEX improves substantially the properties of cement-based adhesives for the application of coverings on radiant heating floorings.

Surface preparation

Not necessary.

Modes of application

- Homogenize the content of the package.
- Mix with water in proportion of 1l of TEAIS TERMIC LATEX by each 2 litres of water and mix the cement-base adhesive with this admixture.
- Not apply at temperatures below of 8°C and over 25°C.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



Clean up

Tools must be cleaned with water.

Data sheet

Colour/smilky white

Density 1,05 kg/l

Solid content > 40%

Performance

1 litre per 2 litre of water.

Storage

3 years in their original packages tightly closed and stored in cool and dry place.

Security

Supplementary information:

EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

