TEAIS SULFOR, Additive for improving the resistance to sulphates.



Descripción

TEAIS SULFOR is liquid additive based on copolymers and inorganic compound which improves the resistance to mortar and concrete sulphates. The mixing-water must be added in the elaboration process of mortar and concrete.

Aplication

TEAIS SULFOR is suitable for requirements of resistance in mortar and concrete to seawater, marine environment, sulphates, etc

Surface preparation

Not neccessary.

Modes of application

Shake the content of the package before using.
- Add mixing water in proportion of 2% of cement weight.
- High quality mortar and concrete must be used and with a suitable cement contained.
- It is advisable that A/C relation be less than 0,5.

Clean up

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

With plenty of water.

Data sheet

Color(s)Milky white

Density1,06 kg/lt

Performance

2% of cement weight

Storage

One year in their original packages tightly closed protected from the weather and stored in cool and dry places.

Security

Supplementary information:

EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: