



# TEAIS SULFOR, Additive for improving the resistance to sulphates.

## Description

TEAIS SULFOR is liquid additive based on copolymers and inorganic compound which improves the resistance to mortar and concrete sulphates. The mixing-water must be added in the elaboration process of mortar and concrete.



## Aplication

TEAIS SULFOR is suitable for requirements of resistance in mortar and concrete to seawater, marine environment, sulphates, etc

## Surface preparation

Not necessary.

## Modes of application

- Shake the content of the package before using.
- Add mixing water in proportion of 2% of cement weight.
- High quality mortar and concrete must be used and with a suitable cement contained.
- It is advisable that A/C relation be less than 0,5.

## Clean up



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:



With plenty of water.

# Data sheet

Colour/sMilky white

Density1,06 kg/lit

## Performance

2% of cement weight

## Storage

One year in their original packages tightly closed protected from the weather and stored in cool and dry places.

## Security

## Supplementary information:

EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teis.es](mailto:desarrollo@teis.es)

síguenos en:

