FIBRAIS 150, FIBERGLASS FOR REINFORCING WATERPROOFING AND POLYESTER ROLLED



Description

Fiberglass in yarn shape joint between them by a bonding agent. Suitable for reinforcing waterproofings. It has a good deformability, adaptation to surface of application, a fast impregnation and easy handling.

Aplication

FIBRAIS-150 is an reinforcement designed to improve the mechanical properties of laminates and waterproofing based on polyester resin, elastomer resins, etc. Especially when dimesional and singular points needed stability.

Surface preparation

The surface of application should be clean without any trace of strange particles.

Modes of application

It can be applied onto complex structures.
- It enables quick and easy impregnation, which is possible owing to the length of the threads and the high solubility of the resin based binder, in absence of

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

bubble formation.

Clean up

Clean using large amounts of water.

Data sheet

Density150 grs/sqm

Moisture content< 0,2%

Color(s)white translucent

Tensile Strength120 N/150 mm

Compositionfiberglass

Performance

1,05 m2 per sqm

Storage

It is recommended to store this product in its original rolls being well packed and stored at stable temperatures, ranging in between 15 and 25ºC and 45 to 65% of relative humidity. No limit time for storage.