



# VELOAIS ESPECIAL, SYNTHETIC REINFORCEMENT TO REINFORCE WATERPROOFING.



## Description

## Aplication

In indoors and outdoors both new building and restoration. In humid or dry enviroment but always with suitable paints for the required use.

## Surface preparation

Not necessary

## Modes of application

Apply a suitable base of paint.

Being the paint wet add VELOAIS by a foam roller avoiding air pockets and wrinkles.

Repeat successively overlapping VELOAIS from 2 to 3 cm between them ( in waterproofing) or simply stop (in



decoration).

When the set paint-VELOAIS dry finishing with two hands of smooth paint or rough.

## Clean up

---

Not necessary.

## Data sheet

---

Density 30 gr/m<sup>2</sup>

Elongation until breaking point 35%

Resistance to longitudinal tear >2 daN

Resistance to traction 3,5 daN.

Average thickness 0,31 mm.

Softening point +140 a +150°C

## Storage

---

In their original rollers. In dry place protected from the weather keeps indefinitely.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email: desarrollo@teais.es

síguenos en:

