



## Descripción

Liquid retardant of surface setting-time for faced aggregate pavements. It is applied pure or diluted with water in equal proportion in abundant quantity on the pavement just poured.

## Aplication

To obtain a faced aggregate-finished in decorative pavements or increases the superficial setting-time on concretes which a texture is required.

## Surface preparation

It is no necessary.

## Modes of application

Shake the product before using to homegenize it properly.

- Apply the product by a sprayer.

Once it is concreted apply LAIS with the sprayer before the concrete sets or when the surface water-shine can't be seen on it.

24 hours later approximately according with the weather the surface must be cleaned with water jet and a

brush to obtain the desired texture.

## Clean up

With plenty of water.

## Data sheet

Density 1,06 Kg./Lt.  $\pm$  0,05 kg/Lt

Aspect Liquid appearance in brown colour

Solubility Soluble in water.

## Performance

200 to 400 cc/sqm

## Storage

1 year in their original packages and tightly closed, protected from the weather and in dry and open-air places.

## Security

## Supplementary information:

EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

