

MORIS SULFORRESISTENTE RAPIDO,



Description

Thixotropic mortar without retraction specially designed for repairing. Suitable for the restauration of damaged surfaces by iron oxide spreading. It protect the metallic armours combined with TEAIS PROTECOR and working properly with concrete in the face side. It has a big resistance from the compression. Colour: cement grey.

Aplication

Modes of application

Data sheet

Water absorption


Mass of density

Compressive resistance

Adherence


Performance





Telf.: 981 602 111







Storage

Security





Indications of danger:

H315: H315: Causes skin irritation.

H317: H317:May cause an allergic skin reaction.

H318: H318: Causes serious eye damage.

H335: H335: May cause respiratory irritation.

Prudence advice:

P271: P271Use only outdoors or in a well-ventilated area.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: P302+P352:IF ON SKIN: Wash with plenty of soap and water.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: P310: Immediately call a POISON CENTER or doctor/physician.

P403+P233: P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: P501:Dispose of contents/container in accordance with local/regional/national/international regulation





Email.: desarrollo@teais.es