



# ROCAMOL RUSTICO, CRUSHED ROCK WITH RUSTIC FINISHING FOR NATURAL STONE REFURBISHMENT.



## Description

ROCAMOL RÚSTICO is a powder product consisting of cement, lime, crushed rock, additives, colourings that mixed with water form a material that imitates stone and if is finished by a trowel turn an appearance similar to rustic stone. COLOURCHART REFERENCE:50, 60, 70, 80.  
25 KG sack.

## Aplication

ROCAMOL RÚSTICO is used for imitating texture and colour in existing stone that require refurbishment or to render single coat, combined or complementary.

## Surface preparation

The support must be clean, firm, resistant, free of greases, oils or polluting agents and must be slightly wet.

## Modes of application

ROCAMOL RÚSTICO is mixed with water in proportion of 180 cc of water per kg of product ( from 4,5 to 5 lt of water per ROCAMOL bag).

- The admixutre can be done manually or low revolution electric mixer (300-400 rpm) and helicoidal pallet.
- The material must be spread with trowell or pallet according with the areas to cover, then it must be



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:



regularised and let it get mechanical resistance to allow a texturization treatment by a trowel that provide a characteristic rustic appearance.

## Clean up

Tools must be cleaned while the product is wet. If it hardens only can be cleaned by mechanical means.

## Data sheet

Water absorption 18 +/- 2%

Powder density 1.400 +/- 0,05 g/cc

Mass of density 1.850 +/- 0,05 g/cc

Water retention > 97%

Compressive resistance 55 kg/cm<sup>2</sup>

Flexural strength resistance 12 kg/cm<sup>2</sup>

Adherence > 5 kg/cm<sup>2</sup>

Colour/s According colour chart

## Storage

2 years in their original packages tightly closed, protected from the weather and stored in cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

