ROCAMOL RUSTICO, CRUSHED ROCK WITH RUSTIC FINISHING FOR NATURAL STONE REFURBISHMENT.



Description

ROCAMOL RÚSTICO is a powder product consiting of cement, lime, crushed rock, additives, colourings that mixed with water form a material that imitates stone and if is finished by a trowel turn an appearance similar to rustic stone. COLOURCHART REFERENCE:50, 60, 70, 80.
25 KG sack.

Aplication

ROCAMOL RÚSTICO is used for imitating texture and colour in existing stone that require refurbishment or to render single coat, combined or complementary.

Surface preparation

The support must be clean, firm, resistant, free of greases, oils or polluting agents and must be slightly wet.

Modes of application

ROCAMOL RÚSTICO is mixed with water in proportion of 180 cc of water per kg of product (from 4,5 to 5 lt of water per ROCAMOL bag).
- The admixutre can be done manually or low revolution electric mixer (300-400 rpm) and helicoidal pallet.
- The material must be spread with trowell or pallet according with the areas to cover, then it must be

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

regularised and let it get mechanical resistance to allow a texturization treatment by a trowel that provide a characteristic rustic appearance.

Clean up

Tools must be cleaned while the product is wet. If it hardens only can be cleaned by mechanical means.

Data sheet

Water Absorption18 +- 2%

Powder Density1.400 +- 0,05 g/cc

Bulk Density1.850 +- 0,05 g/cc

Water Retention> 97%

Compressive Strength55 kg/cm2

Flexural Strength12 kg/cm2

Adhesion> 5 kg/cm2

Color(s)According colourchart

Storage

2 years in their original packages tightly closed, protected from the weather and stored in cool and dry place.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: