



ROCAMOL RUSTICO, CRUSHED ROCK WITH RUSTIC FINISHING FOR NATURAL STONE REFURBISHMENT.



Descripción

ROCAMOL RÚSTICO is a powder product consisting of cement, lime, crushed rock, additives, colourings that mixed with water form a material that imitates stone and if is finished by a trowel turn an appearance similar to rustic stone. COLOURCHART REFERENCE:50, 60, 70, 80.
25 KG sack.

Aplication

ROCAMOL RÚSTICO is used for imitating texture and colour in existing stone that require refurbishment or to render single coat, combined or complementary.

Surface preparation

The support must be clean, firm, resistant, free of greases, oils or polluting agents and must be slightly wet.

Modes of application

ROCAMOL RÚSTICO is mixed with water in proportion of 180 cc of water per kg of product (from 4,5 to 5 lt of water per ROCAMOL bag).

- The admixutre can be done manually or low revolution electric mixer (300-400 rpm) and helicoidal pallet.
- The material must be spread with trowell or pallet according with the areas to cover, then it must be



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



regularised and let it get mechanical resistance to allow a texturization treatment by a trowel that provide a characteristic rustic appearance.

Clean up

Tools must be cleaned while the product is wet. If it hardens only can be cleaned by mechanical means.

Data sheet

Water absorption 18 +/- 2%

Powder density 1.400 +/- 0,05 g/cc

Mass of density 1.850 +/- 0,05 g/cc

Water retention > 97%

Compressive resistance 55 kg/cm²

Flexural strength resistance 12 kg/cm²

Adherence > 5 kg/cm²

Colour/s According colour chart

Storage

2 years in their original packages tightly closed, protected from the weather and stored in cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

