



MORIM, PRE-DOSED MORTAR WITH WATERPROOFING PROPERTIES



Descripción

Pre-dosed product with waterproofing properties for making outdoor renders, brick or block fixing, etc. The product is presented such as powder and water is added for the application.

Aplication

It is used in traditional renders, for setting up brick walls, concrete block walls, in basements, etc.

Surface preparation

The background of application must be clean, free of dust, loose particles, grease and oil. It is recommended to previously dampen the support in summer under high temperatures.

Modes of application

Mix MORIM with water (approximately 200 cc for every kg of MORIM).

- Mix manually or by using a low speed mixer(300 to 400 r.p.m.).
- Before the application, leave to stand for 2 to 5 minutes.

Apply it using a trowel in a conventional manner getting a floated finish.

Clean up



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



Clean using large amounts of water.

Data sheet

Water absorption 18 + - 2%

Adherence > 10 kg/cm²

Colour/s White and grey

Compressive resistance Aprox. 150 kg/cm²

Flexural strength resistance > 35 kg/cm²

Powder density 1,40 +/- 0,05 gr/ml

Mass of density 2,05 +/- 0,05 gr/ml

Curing density 1,80 +/- 0,05 gr/ml

Temperature of work 5 to 30°C

Performance

2 kg/sqm per each mm of thickness

Storage

It is recommended to store this product for 2 years in its tightly closed original packages protected against bleakness.

Security



Indications of danger:

H315: H315: Causes skin irritation.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



H317: H317:May cause an allergic skin reaction.

H318: H318:Causes serious eye damage.

H335: H335:May cause respiratory irritation.

Prudence advice:

P261: P261:Avoid breathing dust/fume/gas/mist/vapours/spray.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: P302+P352:IF ON SKIN: Wash with plenty of soap and water.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: P321:Specific treatment (go to see a doctor with the Safety data sheet for this product).

P405: P405:Store locked up.

P501: P501:Dispose of contents/container in accordance with local/regional/national/international regulation



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teis.es

síguenos en:

