PLASTOCAL, POWDER PRODUCT USED FOR PLASTERING



Descripción

PLASTOCAL is a powder product for plastering. It is mixed with water so as to form an adequate paste used for plastering, smoothening and eliminating cracks or chippings in exterior and interior supports, both vertically and horizontally.

Aplication

It is used to eliminate all kinds of irregularities so as to prepare supports before painting them, both in interiors and exteriors. It is appropriate for levelling of renders, for eliminating cracks and fissures on walls and ceilings.

Surface preparation

The background of application must be clean, with no trace of grease, loose parts, being consistent, firm, cured and dry.

Modes of application

Mix PLASTOCAL with water in a clean container until reaching the desired consistency.
- Make the mix uniform and leave to stand for at least 10 minutes.
- Apply using a smooth trowel or spatula.

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

- When sealing, use TEAIS paints, being compatible, and leave for at least 50 hours since the last application.

Clean up

Clean using large amounts of water whilst the material is still fresh.

Data sheet

Water Absorption50 ± 10%

Adhesion> 0.5 N/mm2

Color(s)white and grey

Curing Density1.500 ± Kg/l

Compressive Strength> 90 kg/cm2

Flexural Strength> 20 kg/cm2

Water Retention> 97%

Working temperature5 to 30ºC

Performance

1.5 kg/m2 in 1 mm thick coating.

Storage

It is recommended to store this product for 2 years in tightly closed original packages.

Security



Indications of danger:

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

H315: H315:Causes skin irritation.

H317: H317:May cause an allergic skin reaction.

H318: H318:Causes serious eye damage.

H335: H335:May cause respiratory irritation.

Prudence advice:

P261: P261:Avoid breathing dust.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: P302+P352:IF ON SKIN: Wash with plenty of soap and water.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: P321:Specific treatment is urgently needed (go to see a doctor with the Safety data sheet for this product).

P405: P321:Store locked up.

P501: P405:Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: EUH208:Contains cement, portland, chemicals. May produce an allergic reaction.