MORPI BASE CEMENTO, CEMENT-BASE MORTAR FOR PLACING AND GROUTING.



Description

Cement-based mortar specially formulated to be applied in block joints, stone, outdoor rendering, etc... MORPI BASE CEMENTO is thixotropic and has waterproofing properties. Colours according colourchart.

Aplication

In laying of mansory. For wall erecting, in grouting of walls and facades, in works where promptness is required.

Surface preparation

Must be clean, free of dust, loose particles, greases, oils and slightly wet.

Modes of application

Mix with water until achieve a thixotropic dough. Admixture must be done manually or by mechanical means with a low revolution electric mixer (300 to 500 rpm).
- After blending let it stand from 2 to 5 minutes before using.
- The application must be done by pallet.
- In case of mansory grouting the use of APLIJUN special grouting gun is very useful allowing a higher filling

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

capacity and accourating application.
- Hardened mortar has waterproofing properties and is permeable to water vapour.

Clean up

Tools must be done while the material is wet. When it hardens only can be removed by mechanical means.

Data sheet

Water Absorption19 +- 3%

Adhesion> 0,5 N/mm2

Capillarity< 0,50% 60 minutos

Curing Density1,80 kg/cm3

Bulk Density1,75 kg/cm3

Powder Density1,35 kg/cm3

Compressive Strength> 80 kg/cm2

Flexural Strength> 35 kg/cm2

Water Retention> 97%

Working temperaturefrom 5 to 30ºC

Performance

18 to 20 kg/sqm cm

Storage

Two years in their original packages protected from the weather and stored in cool and dry place.