EMPLASCEM, HIGH ADHERENCE PLASTER FOR REGULARIZING SURFACES MADE OF TILE.



Descripción

High adherence plaster special for regularizing surfaces made of tile or glazed.
It is a two-component product which both components must be blended before applying. After the product application the surface can be finished with paints, wallpaper, etc?

Aplication

EMPLASCEM is used for regularizing surfaces with bad adherence such as tile, brick, glazed, chipboard and several supports that want to be homogenized.

Surface preparation

The support must be firm, free of greases, oils or any substance that may pollute the surface and well dry. Concretes and mortars must be cured at least for 28 days.

Modes of application

Mix the liquid component manually or mechanically with the powder until obtaining a thixotropic paste with consistence.
- The mixture must be done manually or by a low-revolution electric mixer (300-500 rpm).

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

- Let the dough rest from 2 to 5 minutes before using.
-Apply with a stainless- stell trowel on the clean and dry support giving a thin first layer to cover all joints of the pieces.
- Let it dry and apply the finishing layer that can be sanded once it had hardened to remove smalls shapes made for the trowel.
- Let it dry before painting, wallpapering, etc.

Clean up

The tools must be cleaned with plenty of water while the material is wet.

Data sheet

Water AbsorptionOf powder component = 30 +- 5%

Adhesion> 0,5 N/mm2

Bulk Density1,76 kg/lt

Powder Density0,85 kg/lt

Mix ratio3 parts powder component 1 part liquid component

Open Time> 20 minutes at 20ºC

Performance

1,5 to 2 kg/sqm

Storage

2 years in their original packages tightly closed, protected from the weather.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: