



## Descripción

Microconcrete of quick setting and suitable resistance for repairing asphalt agglomerate pavements. Available in black colour which made possible to hide the difference between colours.

## Aplication

Duroasfalt is used to make repairs on asphalt pavements.

## Surface preparation

The substrate must be clean, free of dust and loose particles and dry .

## Modes of application

It is mixed with water to form a thixotropic consistency mortar.

- Extends the previously prepared hole, compacting it with a shovel or pallet.
- It is leveled if necessary and to give proper texture.
- In hot weather it is convenient to keep damp permanently, at least the first 72 hours.

## Clean up

The tools are cleaned with water before the product hardens.

# Data sheet

---

Colour/sblack

Adherence > 0,5 N/sqmm

Compressive resistance > 80 kg/sqm

Curing density > 1,6 kg/lt

## Performance

---

20 kg/sqm per 1 cm thickness

## Storage

---

Two years in their original containers stored in a cool dry place, protected from the weather.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

