



TEAIS ALISADOR MONOCAPAS, Special mortar to smooth scraped one-layer mortars.



Descripción

TEAIS ALISADOR MONOCAPA is a special mortar for levelling facades of scraped one-layer mortar wanted to be repaired and smoothed and paint them later. This fine layer mortar has high adherence with scraped one-layer mortar and once them dry can be painted on. The advantage of using this system of one-layer repairing is that subsequently repairs needed will be done easily.

Aplication

The main application is the smoothing and levelling of scraped one-layer mortar.

Surface preparation

The support must be clean, free of dust, loose particles or any other substance that hinder the adherence.

Modes of application

- Firstly, repair fissures and cracks using TEAIS GRAP system.
- In areas where the material is loose or with low resistance, chip it and repair.
- TEAIS ALISADOR MONOCAPA is prepared by mixing with water manually or mechanically (low-revolution electric mixer) until achieve a dough and thixotropic consistence.
- The application must be done by stainless steel and can be smoothed to achieve a surface as smooth as



possible.

- Once it dries can be painted on with outdoor paints as REVETAIS and ACRILAIS.

Clean up

Tools must be cleaned with plenty of water while the material is wet.

Data sheet

Performance

1,8 kg/sqm per mm of thickness.

Storage

One year in their original packages protected from the weather, stored in cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email.: desarrollo@teais.es

síguenos en:

