



HIDROXIDO DE CAL CL 90-S, Lime hydroxide, lime hydrate, slaked lime.



Descripción

Powder lime dryhydroxide to use as a mortar conglomerating (CL 90 S).

Aplication

Suitable as a mortar conglomerating for several applications mainly in restoration, eco-building, water for human consumption treatment, remineralisation of desalinated water, sludge treatment in purifiers, incinerations plants, gas treatment, disinfection of henhouses, fruits and vegetables preserving, milk-industry, etc...

Surface preparation

According use

Modes of application

When it is used as a conglomerating must be mixed with water and sand in several proportions.
- Also can be mixed with sand, cement and water.

Clean up



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



With water

Data sheet

Compositionlime hydroxide

Densityin bulk 300 to 600 kg/m³

Aspectwhite dry powder

Storage

One year in their original packages tightly closed protected from the weather and stored in cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

