



TEAIS BACHES, POTHOLE REPAIRING OVER GROUND AND SCREEDS.

Descripción

System of products for potholes on pavements composed for a powder product which blended with water made a fluid mortar and gravel with a particle-size of 10-20.

Very suitable for filling potholes in all types of pavements. It a fast, versatile and inexpensive system.

Aplicación

TEAIS BACHES is used to make quick, firm and affordable fillings, on parking concrete floorings, paths, industrial areas, etc...

Surface preparation

The support must be compact and without water (can be wet).

Modes of application

The product comes powdered and is mixed with 4,5 lts of water with that a mortar is achieved with grouting consistence. The application is done just after the done admixture without letting it stand.

- Potholes must be prepared by filling it with gravel with a particle size between 20 and 40 m. Compact the gravel in pothole.
- Pothole must have a depth of 6 cm and in some cases can reach 10 cm.
- For higher thickness the reparation can be done in two layers (gravel+ TEAIS BACHES and gravel+ TEAIS BACHES).
- Fluid mortar must be poured slowly on the smooth gravel in order to fill hollows and compact good as well.
- To improve the finishing a spiked roller must be used when the material is just applied.
- Let it stand for 4 hours on summer and 8 on winter to can walk on repairs.

Clean up

Tools must be cleaned with water while the material is wet.

Data sheet



Curing density 1,8 kg/lt

Composition cement, additives, compensated fine aggregates

Aspect fluid grouting

Performance

Gravel 18 kg/lt Mortar 14 kg/lt

Storage

Two years in their original packages tightly closed, protected from the weather and stored in cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email: desarrollo@teais.es

síguenos en:

