



Descripción

Thin-bed levelling paste for indoors for thickness until 5 mm based on cement and special charges, plasticizer and additives (don't use for outdoors or areas with permanent damp).

Aplication

It is used for levelling indoor floorings with thickness until 5 mm. In areas free of permanent damp.

Surface preparation

The support must be dry, firm, free of dust or loose particles. In porous supports the application of a primer layer with IMPRIMAIS MU is required.

Modes of application

- Mix with water until obtain a fluid consistence mortar.
- It allows the application of layers until 5 mm of thickness.
 - In porous supports a primer layer must be applied.
 - In smooth supports thinner thickness can be applied.
 - Apply with temperatures over 5°C and below of 30°C

Clean up

Tools must be cleaned with plenty of water while the material is wet.

Data sheet

Water absorption 6 litres of water per 25 kg of dust approximately.

Compressive resistance 190 kg/cm²

Resistance to longitudinal tear 60 kg/cm²

Adherence > 1 N/mm²

Performance

1,5 kg/sqm per 1 mm of thickness.

Storage

Two years in their original packages protected from the weather, stored in dry places.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

