



TEAIS PLASTOCEM, PUTTY FOR FILLING AND REPAIRING FOR OUTDOOR.



Description

Mortar for filling, smoothing and repairing for preparing supports to be painted. It is applied on supports with or without paint. It is a product with high adherence and fast hardening.

Aplication

The product is applied to prepare external wall for further painting and re-painting.

Surface preparation

The support must be clean and dry, free of dust and loose particles, firm and with good cohesion.

Modes of application

TEAIS PLASTOCEM is mixed with water in doughy consistency.

- Apply by stailless stell or plastic trowel or spatula.
- Don't apply on polystirene or wet supports.
- Don't apply under direct sunlight or hot surfaces.
- Don't apply with temperatures below 5°C or over 35°C.
- Don't re-mix the dough once it begins to harden.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:



Clean up

Tools must be clean with water while the material is wet.

Data sheet

Water absorption 45% +/- 2

Hard dry from 30 to 45 minutes.

Colour/s white

Adherence > 0,8 N/mm²

Powder density 0,79 +/- 0,05 kg/lt

Performance

1,2 kg/sqm per each 1 mm of thickness.

Storage

Two years in their original packages, protected from the weather and stored in cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

