



# TEAIS PLASTOCEM, PUTTY FOR FILLING AND REPAIRING FOR OUTDOOR.



## Descripción

Mortar for filling, smoothing and repairing for preparing supports to be painted. It is applied on supports with or without paint. It is a product with high adherence and fast hardening.

## Aplication

The product is applied to prepare external wall for further painting and re-painting.

## Surface preparation

The support must be clean and dry, free of dust and loose particles, firm and with good cohesion.

## Modes of application

TEAIS PLASTOCEM is mixed with water in doughy consistency.

- Apply by stainless steel or plastic trowel or spatula.
- Don't apply on polystyrene or wet supports.
- Don't apply under direct sunlight or hot surfaces.
- Don't apply with temperatures below 5°C or over 35°C.
- Don't re-mix the dough once it begins to harden.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:



## Clean up

---

Tools must be clean with water while the material is wet.

## Data sheet

---

Water absorption 45% +/- 2

Hard dry from 30 to 45 minutes.

Colour/swhite

Adherence > 0,8 N/mm<sup>2</sup>

Powder density 0,79 +/- 0,05 kg/lt

## Performance

---

1,2 kg/sqm per each 1 mm of thickness.

## Storage

---

Two years in their original packages, protected from the weather and stored in cool and dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

