



TEAIS TAPAGOTELE, SPECIAL PLASTER FOR COVERING STIPPLED PAINT (GOUTTELETTE).



Descripción

TEAIS TAPAGOTELÉ is a special plaster for smoothing surfaces rendered by stippled paint (gouttelette).

Aplication

TEAIS TAPAGOTELÉ is used for smoothing surfaces rendered with stippled paint.

Surface preparation

The surface must be clean, perfectly dry, free of greases, saltpeter, being compacted and without loose parts.

Modes of application


Stir the content of the package.

- It must be applied by stain-less steel trowel. Let it stand for 48 hours before sanding.
- The application must be done in thin-layer to let it dry properly.
- If filling fissures or cracks are required a previous plaster with the same material must be done before applying the smoothing layer.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



Clean up

With plenty of clean water while the material is wet. Once it hardens only can be removed by mechanical means.

Data sheet

Adherence > 1 N/mm²

Colour/white

Density 1,65 kg/l

Performance

1,5 kg/ sqm per 1mm of thickness.

Storage

2 years in their original packages tightly closed, protected from the weather and stored in cool and dry place.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:

