



LINOXI, STAINLESS STEEL WELDING CLEANER.



Descripción

Cleaner for welding slag in stainless steel. Product in gel consistency that is used for cleaning stainless steel welded areas.

Aplicación

It is used for cleaning surfaces made of stainless steel that were welded.

Surface preparation

The surface must be dry and free of dust.

Modes of application

Homogenize well the product before applying.

- Apply on the surface to be cleaned by brush and let it act for an hour.
- Clean with plenty of water.
- If the cleaning is not enough, the procedure can be done again.

Clean up



With plenty of water.

Data sheet

Density 1,38 kg/lt

Colour/swhitish

Performance

1 lt/ 4 sqm

Storage

Two years in their original packages protected from the weather, stored in cool and dry places.

Security



Indications of danger:

H301: Toxic if swallowed.

H310: Fatal in contact with skin.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H410: Very toxic to aquatic life with long lasting effects.

Prudence advice:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email.: desarrollo@teais.es

síguenos en:

