



LASTOIS CAPA INTERMEDIA, BASE LAYER ELASTOMERIC WATERPROOFING AGENT OF LASTOIS SYSTEM.



Description

Product based on elastomeric resins, additives and pigments of high resistance to water. Effective as waterproofing in decks, facades and exterior walls. It requires LASTOIS FH-CV as a finish. It isn't resistant to sunlight because of it must be protected. Not flammable. Available in light grey colour.

Application

For waterproofing decks, facades and exterior walls in general. As base layer for further finishing with LASTOIS FH-CV in waterproofing systems with medium and high requirements.

Surface preparation

The surface must be clean, free of greases, oils and dust. Perfectly compacted, smooth, uniform and dry.

Modes of application

The content of the package must be homogenized very good.

- It must be applied by brush or short nap roller.
- IMPRIMAIS M.U. must be used to priming (cementitious base).



Avda. da Enerxía, nº 153, PoL Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

Once the primer is dry, apply the first layer of LASTOIS CAPA INTERMEDIA with VELOAIS integrating it by a roller and overlapping them 2 cm.

After that, let it dry and apply the second layer with LASTOIS CAPA INTERMEDIA.

When the second layer is dry, finish with LASTOIS FH-CV. In order to improve the waterproofing one hand of ACRILAIIS TRASLÚCIDA must be applied on it.

- LASTOIS CAPA INTERMEDIA always must be protected thus in its formulation there are not additives resistant to UV.

Clean up

With plenty of clean water while the product is wet.

Data sheet

Density 1,25 Kg./Lt. +- 0,05

Viscosity 25.000 +- 5.000 mPa.s

Colour/slight grey.

Aprox. 400%

Resistance to traction Aprox. 2 N/mm²

Temperature of work From 5 to 30°C

Solubility It can be diluted in water.

Solid content > 60%

Performance

From 1,5 to 2 kg per sqm of 250 microns

Storage

2 years in their original packages and tightly closed, protected from the weather and stored in cool and dry places

Security



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:



Indications of danger:

H412: Harmful to aquatic life with long lasting effects.

Prudence advice:

P273: Avoid release to the environment.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains . May produce an allergic reaction.