



# LASTOIS CAPA INTERMEDIA, BASE LAYER ELASTOMERIC WATERPROOFING AGENT OF LASTOIS SYSTEM.



## Descripción

Product based on elastomeric resins, additives and pigments of high resistance to water. Effective as waterproofing in decks, facades and exterior walls. It requires LASTOIS FH-CV as a finish. It isn't resistant to sunlight because of it must be protected. Not flammable. Available in light grey colour.

## Aplication

For waterproofing decks, facades and exterior walls in general. As base layer for further finishing with LASTOIS FH-CV in waterproofing systems with medium and high requirements.

## Surface preparation

The surface must be clean, free of greases, oils and dust. Perfectly compacted, smooth, uniform and dry.

## Modes of application

- The content of the package must be homegenized very good.
  - It must be applied by brush or short nap roller.
- IMPRIMAIS M.U. must be used to priming (cementitious base).



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:



Once the primer is dry, apply the first layer of LASTOIS CAPA INTERMEDIA with VELOAIS integrating it by a roller and overlapping them 2 cm.

After that, let it dry and apply the second layer with LASTOIS CAPA INTERMEDIA.

When the second layer is dry, finish with LASTOIS FH-CV. In order to improve the waterproofing one hand of ACRILAIS TRASLÚCIDA must be applied on it.

- LASTOIS CAPA INTERMEDIA always must be protected thus in its formulation there are not additives resistant to UV.

## Clean up

With plenty of clean water while the product is wet.

## Data sheet

Density 1,25 Kg./Lt. +- 0,05

Viscosity 25.000 +- 5.000 mPa.s

Colour/slight grey.

Aprox. 400%

Resistance to traction Aprox. 2 N/mm<sup>2</sup>

Temperature of work From 5 to 30°C

Solubility It can be diluted in water.

Solid content > 60%

## Performance

From 1,5 to 2 kg per sqm of 250 microns

## Storage

2 years in their original packages and tightly closed, protected from the weather and stored in cool and dry places

## Security



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teis.es

síguenos en:



## Indications of danger:

---

H412: Harmful to aquatic life with long lasting effects.

## Prudence advice:

---

P273: Avoid release to the environment.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

---

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

